

# 260 D

# **CD** Transport

optional 32-bit DAC



The **Neo 260 D** CD Transport with optional 32-bit DAC is the next evolutionary step in combining high-performance, useful features, CD plauback and music streaming into one chassis.

Borrowing much of its technology from the more exotic and costlier 650D in the Evolution series, the **Nēo 260D** can do it all: Want to stream music from your computer? How about enjoying your favorite satellite movie channels with the audio fidelity of your music system? Or perhaps listen to your Blu-Ray movies with the same fervor as your music collection. Then again, if you simply want to play your favorite CD's, the **Nēo 260D** does that with powerful digital technology that extracts every last musical detail from the disc.

The **Nēo 260D** offers superb flexibility as a result of being a CD Transport and a DAC all-in-one. Thanks to its 32-bit processing engine, upsampling capabilities, hallmark MOON oversized power supplies and elaborate analog stage, the **Nēo 260D**'s sonic performance is without equal in its price category. The DAC section is entirely optional, whereby you can easily add it later on, if not needed right now.

Of course, features you would expect in a MOON Nēo Series product are present such as SimLink™, RS-232 and IR ports for custom-install environments.

### Significant Design Features:

- Proprietary CD drive system mounted on our M-Quattro gel-based
  4-point floating suspension for vibration damping, allowing ambient
  and spatial cues in your recordings to come to life like never before
- Two (2) digital outputs S/PDIF and AES/EBU

## With Optional Digital-to-Analog Converter:

- True 32-bit asynchronous Digital-to-Analog converter
- 4 digital inputs (S/PDIF x 2, TosLink x 1 and USB x 1) allowing for a connection to virtually any digital source
- USB input with galvanic isolation

#### Specifications:

Frequency response (full range)	2Hz - 100kHz +0/-3dB
THD @ 1kHz, OdBFS (A-weighted)	< 0.001 %
Intermodulation distortion	< 0.001 %
Dynamic Range	> 120dB
Bit-depth range (all inputs)	16 - 24 bits
Sampling rate freq. range (all inputs) .	44.1 - 192kHz
Shipping weight	
Dimensions (width x height x depth)	
	$42.9 \times 8.6 \times 33.3$ cm.



Proudly designed and handcrafted in Canada since 1980

www.simaudio.com

1345 Newton Road, Boucherville, QC, J4B 5H2 CANADA 2002 Ridge Road, Champlain, NY 12919 USA sales@simaudio.com 450.449.2212



#### Available Finishes







Silver (optional)



2-Tone (optional)

